

LANDO 1004.02

T.T. RANGE

EN ISO 20345:2022 CE
S3L CI HI HRO FO SR

SIZES EU 35 - 48
UK 2 1/2 - 13
MP 217 - 315

BREATHABLE
LINING



CLIMA
CORK
SYSTEM
TEMPERATURE
AND HUMIDITY
REGULATOR

DIRECTLY
INJECT PU +
RUBBER

NUBUCK
LEATHER



EXTRA
PROTECTION

EXTRA COMFORT SOLE
DIMINISHED FATIGUE,
FASCEITIS AND CLAW



CHARACTERISTICS

SOLE	DIRECTLY INJECT PU + RUBBER
PROTECTIVE TOE CAP	COMPOSITE (impact-resistant up to 200J)
PROTECTIVE MIDSOLE	KEVLAR (perforation-resistant up to 1100 N)
UPPER MATERIAL	NUBUCK WR LEATHER - BROWN
LINNING MATERIAL	VADICONFORT TEXTILE - BLACK
INSOLE	LAVORO X-MAX ANTISTATIC
WIDTH	11



ESD
(ELECTROSTATIC PROTECTION)



CLIMA CORK
SYSTEM



RESISTANT
UP TO 300°C



METAL FREE



FLEXIBLE



WOMAN



SHOCK
ABSORBER



FUEL/OIL
RESISTANT SOLE



ANTI-SLIP
SOLE



WATER
REPELLENT UPPER